

Wabo®Flex SR 2A and SR 2.5A

Design Features

- Exposed riding surfaces are designed w/ aluminum skid resistant plates
- Low profile system
- Designed to prevent debris build-up and allow for a smooth ride

Blockout Dimension Table																
	Α				"B'				"C"							
Model	Min.		Max.		Min.		Max.		Min.		Max.		"ס"		"E"	
Number	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm
SR 2A	10.125	257	12.125	308	7.375	187	9.375	238	1.000	25	3.00	76	1.375	35	1.813	46
SR 25A	13.000	330	15.500	394	9.750	248	12.250	311	1.375	35	3.875	98	1.625	41	2.063	52
		Cc	onsult yo	our W	BARep	resenta	ative wit	hyour	special	desig	n requir	emen	ts.			

PROJECT NAME:

PROJECT LOCATION:

DRAWING DESCRIPTION:

Wabo®Flex

DATE: 04/19/2024 MODEL: SR



Watson Bowman Acme 95 Pineview Drive Amherst, NY 14228 phone: (716) 691-7566 fax: (716) 691-9239 www.watsonbowmanacme.com



REVISION NO:

SHEET NO

AWING NO: C-20524

Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.